EVERCOLD® INSTANT CHILLED WATER SYSTEM

SPECIFICATIONS MODEL # WI-WIC500S

Undercounter water chiller for use with sink mounted dispenser faucet.

- **Refrigeration Capacity:** Chilling capacity of 1.26 Gallons (4.8 Liters) per hour of drinking water, according to standard ARI 1010 (2020).
- Installation: Quick and easy 1/4" push to connect fittings.
- Improved Chilling: Integrated fan for rapid ventilation and temperature recovery.
- Safety Features: Equipped with leak detection and automatic water shut off.
- Cabinet: 304 Stainless Steel.
- Water Temperature Regulation: Cold control located inside cabinet.
- **Cooling Unit:** Maintenance-free 1/10 HP compressor protected by an automatically restarting motor cut-off. The refrigeration system is hermetically sealed to virtually eliminate refrigerant gas leakage.

 Refrigerant Gas: HFC 134a, which offers a zero ODP (Ozone Depletion Potential).

- Waterways: Highest quality lead free NSF approved materials (304 Stainless Steel).
- Refrigeration Tank: 0.6 Gallons (2.25 Liters).
- Electrical Data: 1.8 Amps, 110 Volts, 60 Hz, monophase, 140 W.
- Cord: 6 Ft. long with 3-prong plug.
- Shipping Weight: 23 Lbs.
- Easy access drain plug.
- Supplied with 3 ft. long insulating sleeve for outlet water line.
- Best enjoyed with a quality drinking water system for protection against bad tastes, lead, asbestos, rust, chlorine, cysts, VOC's, TTHM's, and other contaminants.

One Year Limited Parts & Labor Warranty.

Water, Inc. warrants this product to be free from defects in workmanship or materials for a period of twelve months after purchase.



Water, Inc. Electric Air Cooled Water Chillers have been listed by ETL.

WaterInc

waterinc.com

MODEL WI-WIC500S TECHNICAL DATA		
COMPRESSOR TYPE	ST	
VOLTAGE	110 V	
HERTZ	60Hz	
POWER CONSUMPTION	198 Watts	
CURRENT	1.80 Amps	
COMPRESSOR DISPLACEMENT	2.27 CM3	
TESTED AT ROOM TEMPERATURE	90°F	32°C
DELIVERY PER HOUR	1.26 Gal.	Lt. 4.8
WATER OUTLET TEMPERATURE	50°F	10°C
TANK CAPACITY	0.6 Gal.	Lt. 2.25
FITTINGS	1/4" Quick Connect	
REFRIGERANT GAS	R134a	
POWER SUPPLY	115/1/60 (V/n/Hz)	
COMPRESSOR TYPE	Hermetic	
CONDENSER	Air Cooled	
EVAPORATOR	External Tube	
EXPANSION DEVICE	Calibrated Capillary Tube	
CONTROL	Adjustable Thermostat	
DIMENSIONS: WIDTH	16"	
DEPTH	8.5"	
HEIGHT	11.5"	
NET WEIGHT	23 Lbs.	
SHIPPING WEIGHT	27 Lbs.	
SHIPPING DIMENSIONS	21" x 12 3/4" x 16 1/2"	



CERTIFICATION
Conform to UL Standard 399:2017 Ed.+R:23May2019

WI-WIC500S

